

balanced


Microphone

MC2000..


Professional Microphone Cables - MC2000..

- very low capacitance (60 pF/m)
- extremely flexible
- extra heavy overall sheath




 Conductor	stranded bare copper, 28 x 0,10 mm
Cross Section	0.22 mm²
Insulation	PE
Core Arrangement	2 cores + cotton tracers twisted
Shielding	bare copper spiral shield
Outer Jacket	PVC, matt
Overall Diameter	6,5 mm

Leiteraufbau	blanke Cu-Litze, 28 x 0,10 mm
Leiterquerschnitt	0.22 mm ²
Isolation	PE
Aderanordnung	2 Adern + Baumwollfäden verseilt
Abschirmung	blanker Cu-Wendelschirm
Außenmantel	PVC, matt
Außendurchmesser	6,5 mm

 Min. Bending Radius	30 mm
Working Temperature	-20 °C / +70 °C

Min. Biegeradius	30 mm
Betriebstemperatur	-20 °C / +70 °C

 Conductor Resistance	< 85 Ω/km
Capacitance	
Cond./Cond.	60 pF/m
Cond./Shield	110 pF/m
Insulation Resistance	> 100 MΩ x km

Leiterwiderstand	< 85 Ω/km
Kapazität	
Ader/Ader	60 pF/m
Ader/Schirm	110 pF/m
Isolationswiderstand	> 100 MΩ x km

■ SW [black] ■ BL [blue] ■ RT [red]

Order Code Bestell-Nr.	Colour Farbe	Weight Gewicht	Standard Length [m] Standard Längen [m]	Max. Length / Reel Max. Länge / Spule
MC2000SW	black	50 g/m	100 / 500	2500 m
MC2000BL	blue	50 g/m	100 / 500	2500 m
MC2000RT	red	50 g/m	100 / 500	2500 m