


Features

Long Throw optics	Pan- 540°
Total FX Package	Tilt- 265°
Modular Construction	Max Speed Pan (360°)- 3.66s
Fast Service Design	Max Speed Tilt (252°)- 2.59s
Electronic Cooling System Control	Full Color LCD Display W/ Battery Mode
LED Type- 600W Bright White Engine	5-Pin DMX/RDM Connector
LED Hours- 70% Luminous output, 50,000 hrs.	3-Pin DMX/RDM Connector
Active Thermal Control	Powercon Connector
Fan Modes- Normal / Continuous / Studio	Pan and Tilt Locks
RDM Compatible	Integrated Yoke Arm Handles
Control Options- DMX 512/RDM	Indigo Highlighter LED's
DMX Channels- 43	Road Case Included (Single)

Optical



Fixed Color Wheel

6 + Open

- 1- Red
- 2- Blue
- 3- Green
- 4- Orange
- 5- Magenta
- 6- Dark Blue

CMY / CTO- Linear

Lens Defog System

Iris

Zoom-Wash Mode- 5 to 45 degrees

Auto-Focus Function


Animation 1- Rotating

Animation 2- Art FX Glass

Frost

Prism 1- Linear


Prism 2- 3 Facet



Rotating Gobo Wheel 1

6 + Open

- 1- Seashell
- 2- Crescents
- 3- Abstract
- 4- Fracture
- 5- Zebra
- 6- Shower



Rotating Gobo Wheel 2

6 + Open

- 1- Strikes
- 2- Triangles
- 3- Woven
- 4- Dense Foliage
- 5- Ice
- 6- Tunnel

Gobo Dimensions \varnothing { O.D.- 30mm (1.18 in)
Image Area- 25mm (.98 in)

Photometrics

High CRI 6500K

LED Engine Output Lumens*	35,000	29,000
Lumens* -	25,000	20,000
CRI-	>75	>90
Color Temperature-	6500K	6500K

* Lumens as measured by Everfine 2.0 integrating sphere and PMS-80 spectrophotometer. Calibration date March 3, 2014

** 10m distance, Narrow Zoom

Electrical

Input Power Rating- AC 100V - 240V 50/60 Hz


10-4 Amps

Auto Switching Power Supply

Db(a)- 38

Dimensions / Physical

Fixture Dimensions



Fixture Weight- 39.5 Kg (87 Lbs.)

Road Case Gross / Shipping Weight- 85 Kg (187 Lbs.)

Road Case Dimensions-

749mm (29.5 in.) x 521mm (20.5 in.) x 953mm (37.5 in.)

Minimum Distance to Flammable Objects- 0.5m (1.64 ft)

Minimum Distance to Lighted Objects- 1.5m (4.9 ft.)

Operating Temperature- 0 - 45°C (32 - 113°F)

Storage Temperature- -20 - 60°C (0 - 140°F)

Compliance Approvals- CE, ETL

Mounting Options-

The fixture can be truss mounted using 1/4 camlock C-clamp mounting brackets. It can also stand upright on a stable surface.

Available Colors- Black

HES PN- H7010015



HIGH END SYSTEMS
a Barco company

High End Systems
2105 Gracy Farms Lane
Austin, TX 78758 USA

Office and Customer Service: 512-836-2242

Fax: 512-837-5290

Toll Free: 800-890-8989

© 2015, High End Systems, Inc. All specifications subject to change without notice.

Projection Chart

Zoom Range and Distance Chart

